

Heat Transfer Papers 1500 Greenleaf Ave, Elk Grove Village, IL 60007



Single Sided Matte

Product Information Bulletin

Product Description:

Breeze D2F Transfer Film - Coated one side Film for use with DTF Inks and Powder Adhesive Hot or Cold Peel Application Transfer: 10 to 15 seconds @ 325°F with Heavy Pressure (Give it a few seconds to set and then peel for the hot peel - or let it cool down completely for the cold peel. If for any reason the transfer is not peeling correctly, then immediately stop and repress the design and peel from the opposite corner.)

Roll sizes: 60cm × 100cm (23.6" × 328') 120cm × 100m (47.24" × 328') Core: 3" standard core (will fit Epson printers)

Sheet size: 33cm x 54cm (13" x 21")

Medium DTF White Powder: 11b packed

Please note: Sheet samples are packed 'Coated / Print side up'

IMPORTANT

We thoroughly test each of our products on various substrates using different transfer equipment. However, it is impossible for us to duplicate all variables using all substrates and transfer equipment. Therefore, it is essential that you test the paper prior to production using your equipment, methods, and substrate material. Heat presses vary in accuracy. Conduct tests to determine the best time and temperature to use with your equipment. Please keep in mind that the Seller's and Manufacturer's maximum obligation shall be to replace any paper that has proven to be defective. Neither the Seller nor the Manufacturer shall be liable for any injury, direct or consequential, arising out of the use of, or inability to use this paper.

For more information or technical assistance, contact:

The AW Specialty Hotline: Toll-Free 800-882-0386

Fax: 847-981-1353 E-mail: techsupport@awpapers.com

www.awpapers.com



AW Group – The Paper Professionals